



AGM Technology
 ABT Etrek DM Series

Complying standards:

IEC 61982.3: 2001
 IEC 61056.1/2: 2002

4-DM-170

8V170Ah(5hr)



ABT Etrek DM series is deep cycle battery with the capability of high output power, especially for EV use. As with all ABT batteries, all are rechargeable, highly efficient, leak proof and maintenance free.

Mechanical Characteristics

	SI Unit	EN Unit
Length	262mm	10.31inch
Width	180mm	7.09inch
Height	279mm	10.98inch
Total Height	280.5mm	11.04inch
Approx. Weight	36.0kg	79.2lbs

Type of material for container and lids:

ABS Standard (FV0 Optional)




Product Characteristics

- Up to 700 cycles 80% DOD
- Good large current discharge performance
- High gas recombination efficiency
- Maximum charge efficiency
- Low self-discharge rate
- Easy installation and handling

Performance Characteristics

- Rated voltage: 8V (4 cells)
- Rated capacity at 68°F(20°C)
 - 5h rate (34.0A, 10.5V) 170Ah
 - 3h rate(50.0A, 10.5V) 150Ah
 - 1h rate(109.0A, 10.5V) 109Ah
- Internal resistance:
 - 3.0mΩ when fully charged at 68°F(20°C)
- Average self-discharge rate:
 - ≤3% per month 68°F(20°C)
- Maximum discharge current:
 - 1350A(10s) at 68°F(20°C)
- Working temperature range:
 - Discharge: -20~45°C
 - Charge: 5~35°C
 - Storage: 0~40°C
- Charging method:
 - with constant voltage at 68°F(20°C)
 - Maximum charge current: 25A
 - Temperature compensation: -12mV/°C/piece
 - Cycle use: 9.8V/ piece
 - Standby use: 9.4V/ piece

Dimensions/Terminal




Constant Current Discharge Data (Ampere at 20°C/68 °F)

End Volt	10min	20min	30min	45min	1h	1.5h	2h	3h	5h	10h	20h
1.60	396.9	234.9	174.4	135.49	113.67	87.15	72.28	51.38	34.74	18.29	9.374
1.65	388.0	230.3	171.6	133.32	112.01	85.95	71.45	50.87	34.44	18.18	9.328
1.70	377.7	224.7	167.9	130.91	110.51	85.01	70.62	50.40	34.22	18.08	9.287
1.75	369.0	220.5	165.0	129.00	109.05	84.00	70.00	50.00	34.00	18.00	9.250
1.80	344.2	207.4	156.1	122.8	104.3	80.72	67.56	48.48	33.17	17.65	9.107


Constant Power Discharge Data (Watts per cell at 20°C/68 °F)

End Volt	10min	20min	30min	45min	1h	1.5h	2h	3h	5h	10h	20h
1.60	697.2	423.1	320.6	252.9	214.6	166.2	139.14	99.76	68.11	36.08	18.59
1.65	694.0	421.1	319.2	251.1	213.3	165.1	138.48	99.32	67.79	36.02	18.57
1.70	685.2	415.6	315.3	248.6	211.8	164.3	137.72	99.01	67.72	35.99	18.56
1.75	678.7	412.3	312.2	246.6	210.2	163.1	137.14	98.62	67.60	35.95	18.55
1.80	644.5	392.1	297.9	236.3	202.0	157.6	132.8	96.01	66.24	35.33	18.29

Charge performance



Cycle life vs. discharge depth



Contact information

Advanced Battery Technology BV
 Add. New Yorkstraat 14 1175 RD Lijnden Amsterdam, Netherland
 Web: <http://www.abtbatt.com> Email: sales@abtbatt.com

ABT VRLA Battery: Available power range from 26Ah to 3000Ah.

Copy right ABT BV,
 all rights reserved.
 (Edition: Feb.,2021)