

AGM TECHNOLOGY
ABT Enduro EHP Series

EHP12-14

12V 14Ah(10hr)

Complying standards:

IEC60896-21/22 2004
JIS C8704-1 1999
BS-6290:4-1997
JIS C8702-1/2 2003
IEC61427:1999
BS EN 61427:2002



High Performance

The ABT Enduro EHP range of VRLA lead acid batteries have been designed specifically for use in applications which demand the highest levels of security and reliability. With proven compliance to the most rigorous international standards.

Enduro EHP is recognized as premium battery for Telecom/IT, Power Utilities applications. Enduro's reputation for long service life combined with excellent high rate performance also makes it the number one choice for high integrity, high specification UPS systems.

Mechanical Characteristics

	SI Unit	English Unit
Length	181mm	7.13inch
Width	76mm	2.99inch
Height	166mm	6.54inch
Total Height	166mm	6.54inch
Approx. Weight	5.85Kg	12.90lbs
Type of material for box and lids : ABS Standard (FV0 Optional)		


Product Characteristics

- Thick Pb-Ca-Sn alloy grids designed to resist corrosion and prolong life
- Low resistance microporous glass fibre separator
- Low specific acid density
- High integrity pillar seal
- Maintenance-Free Operation
- Low Pressure Venting System
- Low Self Discharge
- U. L. Components Recognition
- Six months shelf life at 20°C
- Design life 12+ years

Performance Characteristics

Nominal Voltage	12V
Number of Cell	6
Nominal Capacity 20°C (68°F)	10 hour rate (1.4A, 10.8V) 14Ah 8 hour rate (1.7A, 10.5V) 13.6Ah 1 hour rate (9.5A, 10.5V) 9.5Ah
Intensity	
Max. Discharge Current	20°C (68°F) 320A(5s)
Short circuit current	915A
Maximum charge current	2.8(20% of rated capacity)
Internal Resistance	Fully Charged battery 20°C (68°F) 13.65mOhms
Mass Energy(Wh/kg)	28.72
Volumic Energy(Wh/L)	73.57
Self-Discharge	3% of capacity declined per month at 20°C(average)
Operating Temperature Range	Discharge -20~60°C Charge -10~60°C Storage -20~60°C
Charge Methods:	Constant Voltage Charge 20°C (68°F) Cycle use 14.04-14.28V Temperature compensation -24mV/°C Standby use 13.44-13.68V Temperature compensation -21mV/°C
Terminal Type	Inserted Thread and bolt M5X φ 12
Torque strength in Nm	12~16
Handle Type	Incorporated
Flame arrester	Yes

Dimensions / Terminal




Constant Current Discharge Data (Amperes at 20°C/68°F)

End Volt. Per Cell	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1h	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60V	50.0	39.0	28.0	23.0	20.0	17.0	15.5	14.1	12.6	11.7	10.8	9.90	8.00	6.10	5.25	4.40	3.55	2.70	2.40	2.10	1.80	1.65	1.50	1.33	0.75
1.65V	47.0	38.0	27.5	22.5	19.6	16.6	15.2	13.8	12.4	11.5	10.7	9.80	7.95	6.10	5.25	4.40	3.55	2.70	2.40	2.10	1.80	1.65	1.50	1.33	0.75
1.70V	44.0	37.0	27.0	22.0	19.2	16.3	14.9	13.5	12.1	11.3	10.5	9.70	7.90	6.10	5.25	4.40	3.55	2.70	2.40	2.10	1.80	1.65	1.50	1.33	0.75
1.75V	41.0	35.0	26.0	21.0	18.4	15.8	14.5	13.1	11.8	11.0	10.3	9.50	7.70	5.90	5.10	4.30	3.45	2.60	2.30	2.00	1.70	1.60	1.50	1.33	0.75
1.80V	38.0	32.0	24.0	20.0	17.5	15.0	13.8	12.7	11.5	10.8	10.0	9.30	7.50	5.70	4.90	4.10	3.30	2.50	2.23	1.97	1.70	1.55	1.40	1.24	0.70


Constant Power Discharge Data (Watts per cell at 20°C/68°F)

End Volt. Per Cell	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1h	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60V	85.5	69.3	51.7	42.8	37.7	32.5	29.8	27.2	24.5	23.0	21.5	20.0	15.9	11.8	10.3	8.67	7.08	5.50	4.83	4.17	3.50	3.17	2.83	2.50	1.42
1.65V	81.2	68.2	51.2	42.3	37.3	32.2	29.5	26.8	24.2	22.7	21.3	19.8	15.8	11.8	10.3	8.67	7.08	5.50	4.83	4.17	3.50	3.17	2.83	2.50	1.42
1.70V	78.6	66.7	50.2	41.3	36.4	31.5	28.9	26.4	23.8	22.4	21.1	19.7	15.7	11.7	10.2	8.67	7.08	5.50	4.83	4.17	3.50	3.17	2.83	2.50	1.42
1.75V	74.3	64.2	48.8	40.2	35.4	30.7	28.3	25.9	23.5	22.1	20.7	19.3	15.4	11.5	10.0	8.50	6.96	5.42	4.78	4.14	3.50	3.17	2.83	2.50	1.42
1.80V	70.3	60.5	46.7	38.3	33.9	29.5	27.3	25.1	22.8	21.5	20.2	18.8	15.0	11.2	9.75	8.33	6.83	5.33	4.69	4.06	3.42	3.13	2.83	2.50	1.42


Constant Current Discharge Curve




Capacity Vs Temperature




Constant Power Discharge Curve



Self Discharge



Floating Charge Voltage Vs Temperature



Contact information

Shandong Sacred Sun Power Sources Co., Ltd.
Add: 1, Shenyang Road, Qufu 273100 Shandong, China
Tel: +86-537-4438 666 extn 6028 Fax: +86-537-4411 936
Website: <http://www.abtbatt.com> E-mail: sales@abtbatt.com

ABT VRLA Battery: Available Power Range From 1Ah to 3000Ah

Copyright SACREDSUN,
All rights reserved.
(Edition: March, 2007)