



AGM TECHNOLOGY
ABT Enduro EHP Series

EHP2-200

2V 200Ah(10hr)

Complying standards:

IEC60896-21/22 2004
BS-6290:4-1997
Eurobat Guide -12 years and longer "long life"



High Performance

The ABT Enduro EHP range of VRLA lead acid batteries have been designed specifically for use in applications which demand the highest levels of security and reliability. With proven compliance to the most rigorous international standards.

Enduro EHP is recognized as premium battery for Telecom/IT, Power Utilities applications. Enduro's reputation for long service life combined with excellent high rate performance also makes it the number one choice for high integrity, high specification UPS systems.

Mechanical Characteristics

| | SI Unit | English Unit |
|--------------------------------------------------------------------|---------|--------------|
| Length | 110mm | 4.33inch |
| Width | 208mm | 8.19inch |
| Height | 242mm | 9.53inch |
| Total Height | 260mm | 10.24inch |
| Approx. Weight | 13.5kg | 29.76lbs |
| Type of material for box and lids : ABS Standard (FV0 Optional) | | |


Product Characteristics

- Thick Pb-Ca-Sn alloy grids designed to resist corrosion and prolong life
- Low resistance microporous glass fibre separator
- Low specific acid density
- High integrity pillar seal
- Maintenance-Free Operation
- Low Pressure Venting System
- Low Self Discharge
- U. L. Components Recognition
- Six months shelf life at 20°C
- Design life 12 years

Performance Characteristics

| | |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal Voltage | 2V |
| Number of Cell | 1 |
| Nominal Capacity 20°C (68°F) | 10 hour rate (20.0A, 1.80V) 200Ah 8 hour rate (24.7A, 1.75V) 197.6Ah 1 hour rate (120A, 1.75V) 120Ah |
| Intensity | |
| Max. Discharge Current | 20°C (68°F) 1100A(5s) |
| Short circuit current | 3200A |
| Maximum charge current | 30A(15% of rated capacity) |
| Internal Resistance | Fully Charged battery 20°C (68°F) 0.58mOhms |
| Mass Energy(Wh/kg) | 29.63 |
| Volumic Energy(Wh/L) | 72.24 |
| Self-Discharge | 3% of capacity declined per month at 20°C(average) |
| Operating Temperature Range | Discharge -20~60°C Charge -10~60°C Storage -20~60°C |
| Charge Methods: | Constant Voltage Charge 20°C (68°F) Cycle use 2.34-2.38V Temperature compensation -3.5mV/°C/unit Standby use 2.24-2.28V Temperature compensation -3.5mV/°C/unit |
| Terminal Type | Inserted Thread and bolt M8X φ 18 |
| Torque strength in Nm | 12~16 |
| Handle Type | Incorporated |
| Flame arrester | Yes |

Dimensions / Terminal




Constant Current Discharge Data (Amperes at 20°C/68°F)

| End Volt. Per Cell | 5min | 10min | 15min | 20min | 25min | 30min | 35min | 40min | 45min | 50min | 55min | 1h | 1.5h | 2h | 2.5h | 3h | 4h | 5h | 6h | 7h | 8h | 9h | 10h | 12h | 24h |
|--------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 1.60V | 546 | 415 | 338 | 287 | 249 | 220 | 197 | 178 | 163 | 149 | 137 | 128 | 97.0 | 78.0 | 65.8 | 55.9 | 44.2 | 36.7 | 31.7 | 27.7 | 25.4 | 22.6 | 20.7 | 17.4 | 8.84 |
| 1.65V | 496 | 380 | 313 | 267 | 234 | 208 | 187 | 170 | 155 | 143 | 132 | 125 | 94.7 | 76.7 | 64.7 | 55.1 | 43.6 | 36.3 | 31.3 | 27.5 | 25.2 | 22.3 | 20.5 | 17.3 | 8.78 |
| 1.70V | 453 | 349 | 289 | 249 | 219 | 196 | 177 | 161 | 148 | 137 | 128 | 122 | 92.2 | 75.3 | 63.8 | 54.4 | 43.0 | 35.9 | 31.0 | 27.3 | 24.9 | 22.1 | 20.4 | 17.1 | 8.73 |
| 1.75V | 396 | 321 | 272 | 237 | 210 | 189 | 172 | 157 | 145 | 134 | 124 | 120 | 90.8 | 74.0 | 62.7 | 53.5 | 42.5 | 35.4 | 30.6 | 27.0 | 24.7 | 21.9 | 20.2 | 17.0 | 8.67 |
| 1.80V | 348 | 298 | 257 | 226 | 202 | 182 | 166 | 152 | 140 | 130 | 121 | 115 | 88.3 | 72.2 | 61.3 | 52.5 | 41.9 | 35.0 | 30.3 | 26.7 | 24.4 | 21.7 | 20.0 | 16.8 | 8.61 |


Constant Power Discharge Data (Watts per cell at 20°C/68°F)

| End Volt. Per Cell | 5min | 10min | 15min | 20min | 25min | 30min | 35min | 40min | 45min | 50min | 55min | 1h | 1.5h | 2h | 2.5h | 3h | 4h | 5h | 6h | 7h | 8h | 9h | 10h | 12h | 24h |
|--------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|------|-----|------|------|------|------|------|------|------|------|------|------|------|
| 1.60V | 796 | 673 | 559 | 487 | 416 | 371 | 332 | 300 | 275 | 257 | 236 | 224 | 173 | 142 | 119 | 102 | 80.9 | 67.9 | 59.1 | 52.8 | 48.9 | 43.7 | 39.8 | 33.7 | 17.7 |
| 1.65V | 731 | 611 | 512 | 449 | 387 | 344 | 310 | 283 | 261 | 244 | 228 | 217 | 166 | 137 | 116 | 99.5 | 79.0 | 66.8 | 58.0 | 52.2 | 48.3 | 43.1 | 39.1 | 33.3 | 17.5 |
| 1.70V | 645 | 560 | 476 | 420 | 363 | 321 | 293 | 268 | 248 | 231 | 218 | 210 | 162 | 133 | 113 | 97.5 | 77.6 | 65.9 | 57.2 | 51.5 | 47.7 | 42.5 | 38.8 | 33.0 | 17.3 |
| 1.75V | 578 | 518 | 444 | 390 | 337 | 301 | 273 | 252 | 236 | 220 | 208 | 201 | 158 | 130 | 110 | 95.5 | 76.2 | 64.6 | 56.5 | 50.9 | 47.1 | 41.9 | 38.3 | 32.6 | 17.0 |
| 1.80V | 531 | 475 | 407 | 360 | 314 | 283 | 260 | 238 | 225 | 212 | 200 | 192 | 153 | 126 | 108 | 93.5 | 74.8 | 63.5 | 55.6 | 50.0 | 46.5 | 41.3 | 37.7 | 32.3 | 16.7 |


Constant Current Discharge Curve




Capacity Vs Temperature




Constant Power Discharge Curve



Self Discharge



Floating Charge Voltage Vs Temperature



Contact information

Shandong Sacred Sun Power Sources Co., Ltd.
Add: 1, Shengyang Road, Qufu 273100 Shandong, China
Tel: +86-537-4438 666 extn 6028 Fax: +86-537-4411 936
Website: <http://www.abtbatt.com> E-mail: sales@abtbatt.com

ABT VRLA Battery: Available Power Range From 7Ah to 3000Ah

Copyright SACREDSUN,
All rights reserved.
(Edition: May, 2011)