

EHP2-225

2V 225Ah(10hr)

Complying standards:

IEC60896-21/22 2004
JIS C8704-1 1999
BS-6290:4-1997
JIS C8702-1/2 2003
IEC61427:1999
BS EN 61427:2002



High Performance

The ABT Enduro EHP range of VRLA lead acid batteries have been designed specifically for use in applications which demand the highest levels of security and reliability. With proven compliance to the most rigorous international standards.

Enduro EHP is recognized as premium battery for Telecom/IT, Power Utilities applications. Enduro's reputation for long service life combined with excellent high rate performance also makes it the number one choice for high integrity, high specification UPS systems.

Mechanical Characteristics

	SI Unit	English Unit
Length	142mm	5.59inch
Width	205mm	8.07inch
Height	242mm	9.53inch
Total Height	260mm	10.24inch
Approx. Weight	15.5Kg	34.17lbs
Type of material for box and lids : ABS Standard (FV0 Optional)		


Product Characteristics

- Thick Pb-Ca-Sn alloy grids designed to resist corrosion and prolong life
- Low resistance microporous glass fibre separator
- Low specific acid density
- High integrity pillar seal
- Maintenance-Free Operation
- Low Pressure Venting System
- Low Self Discharge
- U. L. Components Recognition
- Six months shelf life at 20°C
- Design life 12+ years

Performance Characteristics

Nominal Voltage	2V
Number of Cell	1
Nominal Capacity 20°C (68°F)	10 hour rate (22.5A, 1.80V) 225Ah 8 hour rate (27.6A, 1.75V) 220.8Ah 1 hour rate (146.5A, 1.75V) 146.5Ah
Intensity	
Max. Discharge Current	20°C (68°F)2000A(5s)
Short circuit current	3600A
Maximum charge current	45A(20% of rated capacity)
Internal Resistance	Fully Charged battery 20°C (68°F) 0.58mOhms
Mass Energy(Wh/kg)	29.03
Volumic Energy(Wh/L)	63.88
Self-Discharge	3% of capacity declined per month at 20°C(average)
Operating Temperature Range	Discharge -20~60°C Charge -10~60°C Storage -20~60°C
Charge Methods:	Constant Voltage Charge 20°C (68°F) Cycle use 2.34-2.38V Temperature compensation -4mV/°C Standby use 2.24-2.28V Temperature compensation -3.5mV/°C
Terminal Type	Inserted Thread and bolt M8X φ 18
Torque strength in Nm	12~16
Handle Type	Incorporated
Flame arrester	Yes

Dimensions / Terminal




Constant Current Discharge Data (Amperes at 20°C/68°F)

End Volt. Per Cell	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1h	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60V	630.0	507.3	413.2	343.6	302.7	261.8	230.7	210.3	192.3	178.4	163.6	157.1	104.7	90.0	69.5	63.8	46.6	41.7	36.0	29.5	28.5	23.7	22.7	19.1	10.4
1.65V	586.0	491.7	406.6	341.2	299.9	258.5	229.5	209.0	191.3	176.7	162.4	155.5	102.7	88.4	67.9	63.0	46.5	41.6	35.8	29.1	28.4	23.7	22.7	19.1	10.4
1.70V	528.0	459.0	382.9	324.8	288.0	251.2	223.4	205.0	187.2	174.1	161.0	152.2	102.4	86.7	67.7	62.1	46.2	40.8	35.3	29.0	28.1	23.7	22.6	19.1	10.4
1.75V	467.0	410.7	346.9	299.5	268.4	237.3	209.1	193.7	178.5	164.5	152.6	146.5	98.2	84.3	65.5	60.8	45.0	40.1	34.9	28.9	27.6	23.7	22.6	19.1	10.4
1.80V	396.0	352.6	301.9	266.7	241.4	216.0	189.0	178.9	163.2	153.0	140.3	138.3	94.9	80.2	64.2	58.1	44.4	38.9	33.7	28.7	26.9	23.7	22.5	19.0	10.2


Constant Power Discharge Data (Watts per cell at 20°C/68°F)

End Volt. Per Cell	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1h	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60V	1058	912.3	755.2	631.6	536.7	479.5	423.8	385.4	353.5	328.9	301.9	290.5	194.7	166.1	129.3	120.3	89.2	79.4	68.3	55.6	54.0	46.4	43.8	36.9	20.2
1.65V	996.2	877.9	733.9	619.4	516.8	474.5	417.4	382.3	351.7	326.8	299.7	288.8	193.0	165.3	128.9	119.5	88.4	79.2	68.0	55.6	54.0	46.2	43.8	37.1	20.2
1.70V	924.0	833.7	701.2	598.1	494.4	466.4	403.6	373.9	342.6	320.2	296.5	285.5	191.2	163.6	128.2	117.8	88.0	78.3	67.5	55.6	54.0	46.2	43.8	37.1	20.2
1.75V	831.3	759.3	644.7	560.5	475.4	446.7	386.8	360.7	331.4	306.6	284.7	279.0	183.9	161.2	125.1	116.2	86.2	77.0	67.1	55.6	53.1	46.2	43.6	37.1	20.2
1.80V	736.6	663.5	571.1	507.3	441.8	412.4	352.4	335.1	305.8	286.7	263.8	265.9	179.5	155.5	123.1	112.9	85.7	75.6	65.7	55.5	52.7	46.2	43.6	37.1	19.9


Constant Current Discharge Curve




Capacity Vs Temperature




Self Discharge



Constant Power Discharge Curve



Floating Charge Voltage Vs Temperature



Contact information

Shandong Sacred Sun Power Sources Co., Ltd.
 Add: 1, Shengyang Road, Qufu 273100 Shandong, China
 Tel: +86-537-4438 666 extn 6028 Fax: +86-537-4411 936
 Website: <http://www.abtbatt.com> E-mail: sales@abtbatt.com

ABT VRLA Battery: Available Power Range From 1Ah to 3000Ah

Copyright SACREDSUN,
 All rights reserved.
 (Edition: March, 2007)