

## RGT12-27

12V27Ah(20hr)




The ABT e-Trek RGT is a Standard Commercial battery according to Eurobat Classification with 8-10 years design life for cyclic application. As with all ABT batteries, all are rechargeable, highly efficient, leakage proof and maintenance free.



### Specification

Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity 20°C (68°F)	27Ah @20hr-rate to 1.75V Per cell 25.11Ah @10hr-rate to 1.75V Per cell 22.95Ah @5hr-rate to 1.70V Per cell
Weight	Approx .8.2kg(18.08lb)
Maximum Discharge Current	351A(5S)
Short circuit current	1090A
Maximum charge current	8.1A(30% of rated capacity)
Internal Resistance	Approx. 11 mOhms
Mass Energy(Wh/kg)	39.51
Volumic Energy(Wh/L)	89.23
Operating Temperature Range	Discharge -20~60°C; Charge -10~60°C; Storage -20~60°C
Nominal Operating Temperature Range	20°C±3°C(68°F±5°F)
Float Charging Voltage	13.5 t to 13.8 VDC/unit Average at 20°C(68°F)
Equalization and Cycle Service	14.4 to 15.0 VDC/unit Average at 20°C(68°F)
Self Discharge	ABT batteries can be stored for more than 6 months at 20°C(68°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Insert thread and bolt M6 φ 12
Torque strength in Nm	3-4
Container Material	ABS(UL94-HB) Flammability resistance of UL94-V0 can be available upon request.
Handle Type	Incorporated

### Dimensions / Terminal




### Constant Current Discharge Data ( Amperes at 20°C / 68°F )

End Volt. Per Cell	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	99.90	66.17	49.77	30.00	17.85	10.06	7.300	5.590	4.860	3.140	2.680	1.440
1.65V	94.36	63.59	47.84	28.82	17.29	9.760	7.110	5.410	4.720	3.040	2.620	1.420
1.70V	89.18	60.91	46.17	27.70	16.70	9.500	6.940	5.260	4.590	2.950	2.550	1.400
1.75V	83.03	58.22	44.59	26.40	16.11	9.200	6.780	5.130	4.455	2.850	2.511	1.350
1.80V	77.02	53.97	41.00	24.90	15.70	8.750	6.530	4.940	4.290	2.750	2.400	1.330


### Constant Power Discharge Data ( Watts per cell at 20°C / 68°F )

End Volt. Per Cell	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	163.7	111.5	82.90	52.17	31.06	18.18	13.10	10.08	8.310	5.520	4.790	2.561
1.65V	159.1	109.0	81.17	51.18	30.62	17.91	12.93	9.950	8.230	5.450	4.740	2.543
1.70V	155.5	106.3	79.28	49.95	30.15	17.68	12.76	9.810	8.150	5.360	4.670	2.520
1.75V	149.3	102.9	77.35	48.54	29.67	17.44	12.58	9.680	8.060	5.280	4.620	2.482
1.80V	144.2	97.90	75.54	46.59	29.25	17.18	12.39	9.500	7.930	5.160	4.530	2.460


### Trickle (or float) Service Life




### Capacity Retention Characteristic




### Capacity and Temperature




### Cycle Service Life



### Float Charge Voltage and Temperature



### Terminal Voltage (V) and Discharge Time (20°C/68°F)



### Charging Procedures

Application	Charge Voltage(V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Ranges	
Cycle Use	20°C(68°F)	2.45	2.40~2.50	0.3C
Standby	20°C(68°F)	2.275	2.25~2.30	0.3C

### Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.40
Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

### Contact information

Sandong Sacred Sun Power Sources Co., Ltd.  
Add: 1, Shenyang Road, Qufu 273100 Shandong, China  
Tel: +86-537-4438 666 extn 6028 Fax: +86-537-4411 936  
Website: <http://www.abtbatt.com> Email: [sales@abtbatt.com](mailto:sales@abtbatt.com)

ABT VRLA Battery: Available Power Range From 7Ah to 3000Ah

Copyright SACREDSUN,  
All rights reserved.  
(Edition: May. 2011)