

AGM TECHNOLOGY
ABT PowerLine SGP Series

SGP12-60

12V60Ah(20hr)

ABT PowerLine SGP Series is a general purpose battery according to Eurobat Classification with 10 years design life for standby application. As with all ABT batteries, all are rechargeable, highly efficient, leakage proof and maintenance free.

Complying standards:


IEC 61056-1/2-2002
JIS C8702-1/2-2009



Specification

Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity 20°C (68°F)	60Ah @20hr-rate to 1.75V Per cell 55.5Ah @10hr-rate to 1.75V Per cell 37.5Ah @1hr-rate to 1.60V Per cell
Weight	Approx. 18.75kg(41.34lbs)
Maximum Discharge Current	660A (5 sec)
Short circuit current	2362A
Maximum charge current	18A(30% of rated capacity)
Internal Resistance	Approx. 5.08 mOhms
Mass Energy(Wh/kg)	38.4
Volumic energy(Wh/L)	110.0
Operating Temperature Range	Discharge -20~60°C; Charge -10~60°C; Storage -20~60°C
Nominal Operating Temperature Range	20°C±3 °C (68°F±5 °F)
Float Charging Voltage	13.5 t to 13.8 VDC/unit Average at 20°C(68°F)
Equalization and Cycle Service	14.4 to 15.0 VDC/unit Average at 20°C(68°F)
Self Discharge	ABT batteries can be stored for more than 6 months at 20°C(68°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Insert thread and bolt M6× 16
Torque strength in Nm	8~10
Container Material	ABS(UL94-HB) Flammability resistance of UL94-V0 can be available upon request.
Handle Type	Plastic
Flame arrester	Yes

Dimensions / Terminal




Constant Current Discharge Data (Amperes at 20°C)

End Volt. Per Cell	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h	24h
1.60	180.4	139.2	110.3	67.53	37.50	24.47	17.53	13.57	11.22	7.347	5.789	3.212	2.678
1.65	167.2	131.6	104.6	65.49	36.78	23.69	17.04	13.21	10.82	7.166	5.701	3.161	2.649
1.70	155.8	123.5	99.45	63.29	36.00	22.98	16.60	12.82	10.51	6.994	5.626	3.086	2.615
1.75	143.6	117.0	95.06	61.02	35.17	22.04	16.14	12.39	10.15	6.826	5.550	3.000	2.582
1.80	131.5	110.5	89.80	58.43	34.20	21.18	15.61	11.98	9.810	6.640	5.474	2.918	2.552


Constant Power Discharge Data (Watts per cell at 20°C)

End Volt. Per Cell	5min	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h	24h
1.60	297.0	233.0	184.6	116.6	67.30	43.26	31.14	24.13	19.90	12.95	10.39	5.773	4.81
1.65	283.1	227.6	179.0	114.8	65.90	42.53	30.66	23.78	19.55	12.86	10.30	5.685	4.786
1.70	269.7	219.4	174.4	112.3	64.80	41.77	30.17	23.38	19.24	12.77	10.22	5.606	4.744
1.75	258.1	211.4	170.1	109.8	63.70	40.76	29.59	22.98	18.87	12.67	10.12	5.518	4.703
1.80	239.7	203.3	164.1	105.9	62.10	39.53	28.84	22.46	18.53	12.55	10.02	5.423	4.683


Trickle (or float) Service Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




Terminal Voltage (V) and Discharge Time(20°C68°F)



Charge Voltage depend on the temperature



Capacity depend on the temperature



Charging Procedures

Application	Charge Voltage(V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Ranges	
Cycle Use	20°C(68°F)	2.45	2.40~2.50	0.3C
Standby	20°C(68°F)	2.275	2.25~2.30	0.3C

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.40
Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

Contact information

Shandong Sacred Sun Power Sources Co., Ltd.
Add: No.1, Shengyang Road, Qufu City, Shandong Province, China 273100
Tel: +86-537-4438 666 extn 6027 Fax: +86-537-4411 936
Website: <http://www.abtbatt.com> Email: sales@abtbatt.com

ABT VRLA Battery: Available Power Range From 7Ah to 3000Ah

Copyright SACREDSUN,
All rights reserved.
(Edition: May, 2011)